

Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 4 Revision: 17.12.2015 Printing date 17.12.2015 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: 030 FLIP-FLOP CONTROLLER · Article number: RV400Z333 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Lacquer · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Manufacturer: Kansai Altan Boya San. ve Tic. A.S. Ankara Asfalti 25. Km. TR-35730 Kemalpasa - Izmir TURKEY infosds@kansaialtan.com.tr · Further information obtainable from: Material safety department · 1.4 Emergency telephone number: During working hours: +90 232 870-1277 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07 Skin Irrit. 2 H315 Causes skin irritation. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS07 GHS02 · Signal word Danger · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. · Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 Use explosion-proof electrical/ventilating/lighting/equipment. (Contd. on page 2)





Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 4 Printing date 17.12.2015 Revision: 17.12.2015 Trade name: 030 FLIP-FLOP CONTROLLER (Contd. of page 1) P280 Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P321 Specific treatment (see on this label). P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. SECTION 3: Composition/information on ingredients · 3.2 Chemical characterisation: Mixtures • Description: Mixture of substances listed below with nonhazardous additions. · Dangerous components: CAS: 110-19-0 isobutyl acetate 25-50% EINECS: 203-745-1 🚸 Flam. Liq. 2, H225 Index number: 607-026-00-7 Reg.nr.: 01-2119488971-22 CAS: 1330-20-7 10-<25% xylene EINECS: 215-535-7 🚸 Flam. Liq. 3, H226; 🕦 Acute Tox. 4, H312; Acute Tox. 4, Index number: 601-022-00-9 H332; Skin Irrit. 2, H315 Reg.nr.: 01-2119488216-32 CAS: 141-78-6 2,5-<10% ethyl acetate EINECS: 205-500-4 📀 Flam. Liq. 2, H225; 🕔 Eye Irrit. 2, H319; STOT SE 3, H336 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46 CAS: 100-41-4 ethylbenzene 2,5-<10% EINECS: 202-849-4 🚸 Flam. Liq. 2, H225; 상 STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35 CAS: 108-65-6 2-methoxy-1-methylethyl acetate 0,1-≤2,5% EINECS: 203-603-9 🚸 Flam. Liq. 3, H226 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29 CAS: 123-86-4 n-butyl acetate 0,1-≤2,5% EINECS: 204-658-1 诊 Flam. Liq. 3, H226; 🕦 STOT SE 3, H336 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29 Reaction mass of ethylbenzene and xylene 1-≤2,5% 🚯 Flam. Liq. 3, H226; 🚯 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin İrrit. 2, H315 • Additional information: For the wording of the listed risk phrases refer to section 16.

(Contd. on page 3)





Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Version number 4

Revision: 17.12.2015

Trade name: 030 FLIP-FLOP CONTROLLER

(Contd. of page 2)

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• *After skin contact: Generally the product does not irritate the skin.*

· After eye contact: Rinse opened eye for several minutes under running water.

· After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

• 5.1 Extinguishing media

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters

• Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

• 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

• 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)





Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

*

*

Version number 4

Revision: 17.12.2015

Trade name: 030 FLIP-FLOP CONTROLLER

(Contd. of page 3)

	(Contd. of
SEC1	TION 7: Handling and storage
Ensure Preven Inform Keep ig	ecautions for safe handling e good ventilation/exhaustion at the workplace. et formation of aerosols. eation about fire - and explosion protection: gnition sources away - Do not smoke. t against electrostatic charges.
Storag Requir Inform Furthe Keep c Store i	nditions for safe storage, including any incompatibilities e: $5 \ ^{\circ}C - 40 \ ^{\circ}C$ rements to be met by storerooms and receptacles: Store in a cool location. nation about storage in one common storage facility: Not required. er information about storage conditions: ontainer tightly sealed. n cool, dry conditions in well sealed receptacles. ecific end use(s) No further relevant information available.
SEC1	TION 8: Exposure controls/personal protection
Ingred The pr	ntrol parameters ients with limit values that require monitoring at the workplace: oduct does not contain any relevant quantities of materials with critical values that have to be
	red at the workplace. 20-7 xylene
	⁷ Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
100-41	-4 ethylbenzene
IOELV	/ Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin
108-65	-6 2-methoxy-1-methylethyl acetate
IOELV	⁷ Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm
Additio	Skin
· 8.2 Ex · Person · Genero	
	onal information: The lists valid during the making were used as basis. posure controls al protective equipment: al protective and hygienic measures:
Avoid of	onal information: The lists valid during the making were used as basis. posure controls al protective equipment:

• Recommended filter device for short term use: Combination filter A-P2

(Contd. on page 5) EU





Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Trade name: 030 FLIP-FLOP CONTROLLER

Version number 4

Revision: 17.12.2015

(Contd. of page 4) • Protection of hands: Protective gloves Sensibilisation by the components in the glove materials is possible. *Check protective gloves prior to each use for their proper condition.* The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Use gloves resistant to chemical affects (EN 374) and having CE marking. · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • For the permanent contact gloves made of the following materials are suitable: Butyl rubber, BR Fluorocarbon rubber (Viton) · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Neoprene gloves • As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR • Eve protection: Tightly sealed goggles • Body protection: Use protective clothing that prevents direct contact to skin. · Protective suit antistatic. **SECTION 9: Physical and chemical properties** •9.1 Information on basic physical and chemical properties · General Information · Appearance:

Form:FluidColour:ColourlessOdour:CharacteristicOdour threshold:Not determined.PH-value:Not determined.Change in condition
Melting point/Melting range:Undetermined.

(Contd. on page 6)





Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Version number 4

Revision: 17.12.2015

Trade name: 030 FLIP-FLOP CONTROLLER

	(Contd. of page 5
Boiling point/Boiling range:	77 °C
· Flash point:	18 °C (Closed cup)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	> 370 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
· Explosion limits: Lower: Upper:	1,1 Vol % 10,5 Vol %
• Vapour pressure at 20 •C:	20 hPa
• Density at 20 °C: • Relative density • Vapour density • Evaporation rate	1,04 g/cm³ Not determined. heavier than air Not determined.
• Solubility in / Miscibility with water:	Partly soluble.
· Partition coefficient (n-octanol/wa	<i>iter):</i> Not determined.
· Viscosity: Dynamic: Kinematic at 20 °C:	Not determined. 126 s (DIN 53211/4)
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

·11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 val	ues relevant f	or classification:
---------------	----------------	--------------------

1330-20-7 xylene

Dermal LD50 2000 mg/kg (rabbit)

141-78-6 ethyl acetate

Dermal LD50 >18000 mg/kg (rabbit)

(Contd. on page 7)





Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Version number 4

Revision: 17.12.2015

Trade name: 030 FLIP-FLOP CONTROLLER (Contd. of page 6) 100-41-4 ethylbenzene LD50 Dermal 17800 mg/kg (rabbit) 108-65-6 2-methoxy-1-methylethyl acetate Inhalative LC50/96 h 35,7 mg/l (rat) 123-86-4 n-butyl acetate Dermal LD50 >5000 mg/kg (rabbit) Inhalative LC50/96 h > 21,0 mg/l (rat) · Primary irritant effect: · Skin corrosion/irritation Causes skin irritation. • Serious eye damage/irritation Based on available data, the classification criteria are not met. • Respiratory or skin sensitisation Based on available data, the classification criteria are not met. · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) • Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. • *Reproductive toxicity* Based on available data, the classification criteria are not met. • STOT-single exposure Based on available data, the classification criteria are not met. • STOT-repeated exposure Based on available data, the classification criteria are not met. • Aspiration hazard Based on available data, the classification criteria are not met. **SECTION 12: Ecological information** · 12.1 Toxicity · Aquatic toxicity: No further relevant information available. · 12.2 Persistence and degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. • 12.4 Mobility in soil No further relevant information available. • Additional ecological information: · General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 00 00 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00 packaging (including separately collected municipal packaging waste)

(Contd. on page 8)





Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Version number 4

Revision: 17.12.2015

(Contd. of page 7)

Trade name: 030 FLIP-FLOP CONTROLLER

15 01 10* packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:

×

• *Recommendation: Disposal must be made according to official regulations.*

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR	1263 PAINT RELATED MATERIAL, special provision 640H
IMDG IATA	PAINT RELATED MATERIAL Paint related material
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids. - F-E, <u>S-E</u> A
14.7 Transport in bulk according to Ann Marpol and the IBC Code	nex II of Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 E
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml





Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Version number 4

Revision: 17.12.2015

(Contd. of page 8)

Trade name: 030 FLIP-FLOP CONTROLLER

· UN ''Model Regulation'':

UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640H, 3, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· Department issuing MSDS: Product safety department

· Contact: Ms. Sevde Seza Bozacıoğlu

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. on page 10)





Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2015

Version number 4

Revision: 17.12.2015

(Contd. of page 9)

EU

Trade name: 030 FLIP-FLOP CONTROLLER

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2 Asp. Tox. 1: Aspiration hazard, Hazard Category 1 • * **Data compared to the previous version altered.**

