

Page 1/11

## Safety data sheet ccording to 1907/2006/EC, Article

according to 1907/2006/EC, Article 31 Version number 6 Revision: 21.04.2015 Printing date 21.04.2015 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK · Article number: BA355S2300 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Paint • 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Manufacturer: Kansai Altan Boya San. ve Tic. A.S. Ankara Asfalti 25. Km. TR-35730 Kemalpasa - Izmir TURKEY infosds@kansaialtan.com.tr · Further information obtainable from: Material safety department • 1.4 Emergency telephone number: During working hours: +90 232 870-1277 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. · Classification according to Directive 67/548/EEC or Directive 1999/45/EC F; Highly flammable R11: Highly flammable. · Information concerning particular hazards for human and environment: The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version. · Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2)






Page 2/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015



II I	(Contd. of page
Hazard picto	grams
$\wedge$	
GHS02	
011502	
Signal word	Danger
Hazard state	
H225 Highly	flammable liquid and vapour.
Precautionar	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P240	Ground/bond container and receiving equipment.
P303+P361+	+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse
	skin with water/shower.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
2.3 Other has	zards
<b>Results of Pl</b>	3T and vPvB assessment
PBT: Not app	plicable.
vPvB: Not ap	pplicable.

### SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

 $\cdot$  **Description:** Mixture of substances listed below with nonhazardous additions.

• Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate R10-66-67 � Flam. Liq. 3, H226; � STOT SE 3, H336	10-<15%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	3-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10 Image: R10	3-<10%
	(Co.	ntd. on page 3





Page 3/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

### Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

	(Co	ntd. of page 2)
CAS: 100-41-4	ethylbenzene	<i>1-≤2,5%</i>
EINECS: 202-849-4	🗙 Xn R20-48/20-65; 🔥 F R11	
Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	<ul> <li>Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304;</li> <li>Acute Tox. 4, H332</li> </ul>	
CAS: 112-07-2	2-butoxyethyl acetate	1-≤2,5%
EINECS: 203-933-3	Xn R20/21	
Index number: 607-038-00-2	🚺 Acute Tox. 4, H312; Acute Tox. 4, H332	
Reg.nr.: 01-2119475112-47		
Additional information: For the wording of the listed risk phrases refer to section 16.		

### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:
- Do not inhale explosion gases or combustion gases. Wear fully protective suit.

### SECTION 6: Accidental release measures

 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

• 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents

(Contd. on page 4)





Page 4/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

(Contd. of page 3)

### Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect from heat. Protect against electrostatic charges.*
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage: 5 ℃ 40 ℃
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.

• 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

<i>IOELV</i> Short-term value: 442 mg/m <sup>3</sup> , 100 ppm	
Long-term value: 221 mg/m <sup>3</sup> , 50 ppm	
Skin	
108-65-6 2-methoxy-1-methylethyl acetate	
IOELV Short-term value: 550 mg/m <sup>3</sup> , 100 ppm	
Long-term value: 275 mg/m <sup>3</sup> , 50 ppm	
Skin	
100-41-4 ethylbenzene	
IOELV Short-term value: 884 mg/m <sup>3</sup> , 200 ppm	
Long-term value: 442 mg/m <sup>3</sup> , 100 ppm	
Skin	



<sup>· 8.1</sup> Control parameters



Page 5/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

### Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

12-07-2 2-butoxyethyl acetate	(Contd. of page 4
DELV Short-term value: 333 mg/m <sup>3</sup> , 50 ppm	
Long-term value: 133 mg/m <sup>3</sup> , 20 ppm	
Skin	
dditional information: The lists valid during the making were used as basis.	
2 Exposure controls	
ersonal protective equipment:	
eneral protective and hygienic measures: Wash hands before breaks and at	the end of work.
espiratory protection:	0
ot required.	
a case of brief exposure or low pollution use respiratory filter device. In case	of intensive or longer exposure
se self-contained respiratory protective device.	<i>J</i> <u></u>
ecommended filter device for short term use: Combination filter A-P2	
rotection of hands:	
ensibilisation by the components in the glove materials is possible.	
heck protective gloves prior to each use for their proper condition.	
he glove material has to be impermeable and resistant to the product/ the su	bstance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for	
ne chemical mixture.	I I I I I I I I I I I I I I I I I I I
election of the glove material on consideration of the penetration times, rates	s of diffusion and the
egradation	
Ise gloves resistant to chemical affects (EN 374) and having CE marking.	
laterial of gloves	
he selection of the suitable gloves does not only depend on the material, but	also on further marks of quality
nd varies from manufacturer to manufacturer.	
he selection of the suitable gloves does not only depend on the material, but	also on further marks of quality
nd varies from manufacturer to manufacturer. As the product is a preparatio	
esistance of the glove material can not be calculated in advance and has ther	
pplication.	
enetration time of glove material	
he exact break through time has to be found out by the manufacturer of the p	protective gloves and has to be
bserved.	5
or the permanent contact gloves made of the following materials are suital	ble:
utyl rubber, BR	
luorocarbon rubber (Viton)	
or the permanent contact of a maximum of 15 minutes gloves made of the	following materials are
uitable:	
leoprene gloves	
s protection from splashes gloves made of the following materials are suita	<b>ble:</b> Nitrile rubber, NBR
ye protection:	
Tightly sealed goggles	
ody protection: Use protective clothing that prevents direct contact to skin.	(Contd. on page f

(Contd. on page 6)





Page 6/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

(Contd. of page 5)

Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

· Protective suit antistatic.

**SECTION 9: Physical and chemical properties** · 9.1 Information on basic physical and chemical properties · General Information · Appearance: Fluid Form: Colour: Black · Odour: Characteristic · Odour threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. 124 °C Boiling point/Boiling range: · Flash point: 18 °C (Closed cup) · Flammability (solid, gaseous): Not applicable. 370 °C · Ignition temperature: Not determined. • Decomposition temperature: · Self-igniting: Product is not selfigniting. • Danger of explosion: Product is not explosive. However, formation of explosive air/ vapour mixtures are possible. · Explosion limits: 1.2 Vol % Lower: 7,5 Vol % Upper: • Vapour pressure at 20 °C: 10,7 hPa · Density at 20 °C: 1,59 g/cm<sup>3</sup> Not determined. Relative density Not determined. · Evaporation rate · Solubility in / Miscibility with Insoluble water: · Partition coefficient (n-octanol/water): Not determined. Viscosity: Dynamic: Not determined. Kinematic at 20 °C: 126 s (DIN 53211/4) · Solvent separation test: < 0,5 % 9.2 Other information No further relevant information available.

(Contd. on page 7)





Page 7/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

(Contd. of page 6)

### SECTION 10: Stability and reactivity

· 10.1 Reactivity

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

 $\cdot$  10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity:

· LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate         Dermal       LD50       >5000 mg/kg (rabbit)         Inhalative       LC50/4 h       >21,0 mg/l (rat)         1330-20-7 xylene           Dermal       LD50       2000 mg/kg (rabbit)         108-65-6 2-methoxy-1-methylethyl acetate          Inhalative       LC50/4 h       35,7 mg/l (rat)         100-41-4 ethylbenzene           Dermal       LD50       17800 mg/kg (rabbit)         112-07-2 2-butoxvethyl acetate			
Inhalative         LC50/4 h         >21,0 mg/l (rat)           1330-20-7 xylene	123-86-4 1	1-butyl ace	tate
1330-20-7 xylene           Dermal         LD50         2000 mg/kg (rabbit)           108-65-6 2-methoxy-1-methylethyl acetate         Inhalative         LC50/4 h         35,7 mg/l (rat)           100-41-4 ethylbenzene         Dermal         LD50         17800 mg/kg (rabbit)	Dermal	LD50	>5000 mg/kg (rabbit)
Dermal         LD50         2000 mg/kg (rabbit)           108-65-6         2-methoxy-1-methylethyl acetate           Inhalative         LC50/4 h         35,7 mg/l (rat)           100-41-4         ethylbenzene           Dermal         LD50         17800 mg/kg (rabbit)	Inhalative	LC50/4 h	>21,0 mg/l (rat)
108-65-6 2-methoxy-1-methylethyl acetate           Inhalative         LC50/4 h         35,7 mg/l (rat)           100-41-4 ethylbenzene           Dermal         LD50         17800 mg/kg (rabbit)	1330-20-7	xylene	
Inhalative         LC50/4 h         35,7 mg/l (rat)           100-41-4 ethylbenzene         Dermal         LD50         17800 mg/kg (rabbit)	Dermal	LD50	2000 mg/kg (rabbit)
100-41-4 ethylbenzeneDermalLD5017800 mg/kg (rabbit)	108-65-6 2-methoxy-1-methylethyl acetate		
Dermal LD50 17800 mg/kg (rabbit)	Inhalative	LC50/4 h	35,7 mg/l (rat)
	100-41-4 ethylbenzene		
112-07-2 2-butoxyethyl acetate	Dermal	LD50	17800 mg/kg (rabbit)
	112-07-2 2-butoxyethyl acetate		
Dermal LD50 1580 mg/kg (rabbit)	Dermal	LD50	1580 mg/kg (rabbit)

• Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitisation: No sensitising effects known.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity: No further relevant information available.

· 12.2 Persistence and degradability No further relevant information available.

• Other information:

*The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.* 

- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)





Page 8/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

(Contd. of page 7)

### Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

• Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF
	COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS
	AND PRINTING INKS
08 01 00	wastes from MESU and non-oval of paint and namish

08 01 00 wastes from MFSU and removal of paint and varnish

 08 01 11\*
 waste paint and varnish containing organic solvents or other dangerous substances

 08 00 00
 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

 COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS

 AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 13\* sludges from paint or varnish containing organic solvents or other dangerous substances

15 00 00 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED

15 01 00 packaging (including separately collected municipal packaging waste)

15 01 10\* packaging containing residues of or contaminated by dangerous substances

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	uon	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name · ADR	1263 PAINT, special provision 640H	





Page 9/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

	(Contd. of pag
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
14.7 Transport in bulk according to Anne	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities $(EQ)$	Code: El
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	Maximum nei quanitiy per outer packaging. 1000 mi 3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities $(\widetilde{E}Q)$	Code: El
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

## SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 10)






Page 10/11

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015



(Contd. of page 9) · Hazard pictograms GHS02 · Signal word Danger · Hazard statements H225 Highly flammable liquid and vapour. · Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P240 Ground/bond container and receiving equipment. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations: · Information about limitation of use: Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this

preparation. Exceptions can be made by the authorities in certain cases.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- R10 Flammable.
- *R11 Highly flammable.*
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R38 Irritating to skin.
- *R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.*
- *R65 Harmful: may cause lung damage if swallowed.*
- *R66 Repeated exposure may cause skin dryness or cracking.*

(Contd. on page 11)





Page 11/11

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.04.2015

Version number 6

Revision: 21.04.2015

## Trade name: CARDEA 4+1 ACRYLIC PRIMER, BLACK

	(Contd. of page 10)
<i>R67</i> Vapours may cause drowsiness and dizziness.	
· Department issuing MSDS: Product safety department	
• Contact: Ms. Sevde Seza Bozacioğlu	
· Abbreviations and acronyms:	
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de j International Transport of Dangerous Goods by Rail)	fer (Regulations Concerning the
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation	
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)	
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreem Carriage of Dangerous Goods by Road)	ent concerning the International
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
Flam. Liq. 2: Flammable liquids, Hazard Category 2	
Flam. Liq. 3: Flammable liquids, Hazard Category 3	
Acute Tox. 4: Acute toxicity, Hazard Category 4	
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2	
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3	
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2	
Asp. Tox. 1: Aspiration hazard, Hazard Category 1	
• * Data compared to the previous version altered.	
	EU

