

Page 1/10

Safety data sheet

according to 1907/2006/EC, Article 31 Version number 10 Printing date 21.12.2015 Revision: 21.12.2015 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L • Article number: TB4100L1 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Application of the substance / the mixture Thinner, Diluent · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Manufacturer: Kansai Altan Boya San. ve Tic. A.S. Ankara Asfalti 25. Km. TR-35730 Kemalpasa - Izmir TURKEY infosds@kansaialtan.com.tr · Further information obtainable from: Material safety department · 1.4 Emergency telephone number: During working hours: +90 232 870-1277 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Flam. Liq. 2 H225 Highly flammable liquid and vapour. GHS07 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Classification according to Directive 67/548/EEC or Directive 1999/45/EC Xn; Harmful R20/21: Harmful by inhalation and in contact with skin. Xi; Irritant *R36/38*: Irritating to eyes and skin. F; Highly flammable *R11*: Highly flammable. · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

(Contd. on page 2)

EU





Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015 Version number 10 Revision: 21.12.2015 Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L (Contd. of page 1) Classification system: The classification is according to the latest editions of the EU-lists, and extended by company and literature data. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: ethyl acetate 4-methylpentan-2-one · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.





Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

	(Co	ontd. of page 2)
EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene X Xn R20/21; Xi R38 R10 Flam. Liq. 3, H226; () Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	25-50%
EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one X Xn R20; Xi R36/37; K F R11 R66 Flam. Liq. 2, H225;	2,5-<10%
EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene Xn R20-48/20-65; F R11 Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	2,5-<10%
EINECS: 224-644-9	3-methoxybutyl acetate Xi R36 Eye Irrit. 2, H319 he wording of the listed risk phrases refer to section 16.	2,5-<10%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- •4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment:
- Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

(Contd. on page 4)





Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

(Contd. of page 3)

SECTION 6: Accidental release measures			
 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information. 			
 SECTION 7: Handling and storage 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. 7.2 Conditions for safe storage, including any incompatibilities Storage: 5 °C - 40 °C Requirements to be met by storerooms and receptacles: Store in a cool location. Information about storage in one common storage facility: Not required. Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles. 7.3 Specific end use(s) No further relevant information available. 			
 SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace. 1330-20-7 xylene IOELV Short-term value: 442 mg/m³, 100 ppm 			
IOELV Short-term value: 442 mg/m , 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin IOELV Short-term value: 208 mg/m³, 50 ppm Long-term value: 208 mg/m³, 50 ppm Long-term value: 83 mg/m³, 20 ppm (Contd. on page 5)			





Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

(Contd. of page 4) 100-41-4 ethylbenzene IOELV Short-term value: 884 mg/m³, 200 ppm Long-term value: 442 mg/m³, 100 ppm Skin · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls • Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. · Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • Recommended filter device for short term use: Combination filter A-P2 • Protection of hands: Protective gloves Sensibilisation by the components in the glove materials is possible. Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Use gloves resistant to chemical affects (EN 374) and having CE marking. • Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. • For the permanent contact gloves made of the following materials are suitable: Butvl rubber, BR Fluorocarbon rubber (Viton) · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Neoprene gloves • As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR · Eye protection: Tightly sealed goggles



(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

*

Version number 10

Revision: 21.12.2015

(Contd. of page 5)

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

• Body protection: Use protective clothing that prevents direct contact to skin.

· Protective suit antistatic.

9.1 Information on basic physical a	nd chemical properties
General Information	
Appearance: Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	77 °C
Flash point:	4 °C (Closed cup)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Explosion limits:	
Lower:	1,1 Vol %
Upper:	11,5 Vol %
Vapour pressure at 20 °C:	97 hPa
Density at 20 °C:	0,87 g/cm ³
Relative density	Not determined.
Vapour density	heavier than air
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Partly soluble.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	9 s (DIN 53211/4)

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)





Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

(Contd. of page 6)

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

141-78-6 ethyl acetate

Dermal LD50 >18000 mg/kg (rabbit)

1330-20-7 xylene

Dermal LD50 2000 mg/kg (rabbit)

108-10-1 4-methylpentan-2-one

Dermal LD50 16000 mg/kg (rab) Inhalative LC50/96 h 8,3-16,6 mg/l (rat)

100-41-4 ethylbenzene

Dermal LD50 17800 mg/kg (rabbit)

Primary irritant effect:

- · Skin corrosion/irritation
- Causes skin irritation.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

(Contd. on page 8)





Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

(Contd. of page 7)

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND
	PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 10*	

15 01 10* packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name ADR	1263 PAINT RELATED MATERIAL, special provision 640D
IMDG IATA	PAINT RELATED MATERIAL Paint related material
14.3 Transport hazard class(es)	
V	
	3 Flammable liquids.
Class Label 14.4 Packing group ADR, IMDG, IATA	3 Flammable liquids. 3 II
Label 14.4 Packing group	3





Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L

	(Contd. of page 8
· 14.7 Transport in bulk according to Anne	x II of
Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIAL
č	PROVISION 640D, 3, II

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

(Contd. on page 10)

EU





Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.12.2015

Version number 10

Revision: 21.12.2015

Trade name: CARDEA UNIVERSAL THINNER 10 (FAST) - 1 L				
(Contd. of page 9)				
H373 May cause damage to the hearing organs through prolonged or repeated exposure.				
R10 Flammable.				
R11 Highly flammable.				
R20 Harmful by inhalation.				
R20/21 Harmful by inhalation and in contact with skin.				
R36 Irritating to eyes.				
R36/37 Irritating to eyes and respiratory system.				
R38 Irritating to skin.				
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.				
R65 Harmful: may cause lung damage if swallowed.				
<i>R66 Repeated exposure may cause skin dryness or cracking.</i>				
R67 Vapours may cause drowsiness and dizziness.				
• Department issuing MSDS: Product safety department				
• Contact: Ms. Sevde Seza Bozacıoğlu				
· Abbreviations and acronyms:				
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International				
Carriage of Dangerous Goods by Road)				
IMDG: International Maritime Code for Dangerous Goods				
IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals				
EINECS: European Inventory of Existing Commercial Chemical Substances				
ELINCS: European List of Notified Chemical Substances				
CAS: Chemical Abstracts Service (division of the American Chemical Society)				
LC50: Lethal concentration, 50 percent				
LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic				
vPvB: very Persistent and very Bioaccumulative				
Flam. Liq. 2: Flammable liquids, Hazard Category 2				
Flam. Liq. 3: Flammable liquids, Hazard Category 3				
Acute Tox. 4: Acute toxicity, Hazard Category 4				
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2				
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3				
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2				
Asp. Tox. 1: Aspiration hazard, Hazard Category 1				
• * Data compared to the previous version altered.				
EU				

