



Safety data sheet according to 1907/2006/EC, Article 31

Version number 8 Revision: 08.05.2015 Printing date 08.05.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CARDEA UNIVERSAL THINNER 20 (STD) 1 L
- · Article number: TB4200L1
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Thinner, Diluent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufacturer: Kansai Altan Boya San. ve Tic. A.S.

Ankara Asfalti 25. Km. TR-35730 Kemalpasa - Izmir

TURKEY

infosds@kansaialtan.com.tr

- · Further information obtainable from: Material safety department
- · 1.4 Emergency telephone number:

During working hours: +90 232 870-1277

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

H225 Highly flammable liquid and vapour. Flam. Liq. 2



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

H332 Harmful if inhaled. Acute Tox. 4 Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



Xn; Harmful

R20/21-65: Harmful by inhalation and in contact with skin. Harmful: may cause lung damage if swallowed.

(Contd. on page 2)





Page 2/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 1)



Xi; Irritant

R36/37/38: Irritating to eyes, respiratory system and skin.



F; Highly flammable

R11: Highly flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· 2.2 Label elements

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xn Harmful F Highly flammable

· Hazard-determining components of labelling:

Hydrocarbons, C9 aromatics xylene

· Risk phrases:

11 Highly flammable.

20/21 Harmful by inhalation and in contact with skin.

36/37/38 Irritating to eyes, respiratory system and skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· Safety phrases:

- 9 Keep container in a well-ventilated place.
- 15 Keep away from heat.
- 23 Do not breathe gas/fumes/vapour/spray.

36/37 Wear suitable protective clothing and gloves.

- 51 Use only in well-ventilated areas.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.
- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)

EU





Page 3/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 2)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Xn R20/21; Xi R38 R10 → Flam. Liq. 3, H226; → Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	50-75%
CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30	4-methylpentan-2-one Xn R20; X Xi R36/37; F R11 R66 → Flam. Liq. 2, H225; → Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H335	20-<25%
EC number: 918-668-5 Reg.nr.: 01-2119455851-35-003	Hydrocarbons, C9 aromatics Xn R65; Xi R37; N R51/53 R10-66-67 → Flam. Liq. 3, H226; → Asp. Tox. 1, H304; → Aquatic Chronic 2, H411; → STOT SE 3, H335-H336	10-<15%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Xn R20-48/20-65; FR11 Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	3-<10%
CAS: 4435-53-4 EINECS: 224-644-9	3-methoxybutyl acetate Xi R36	3-<10%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

(Contd. on page 4)



— E



Page 4/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 3)

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage: 5 °C 40 °C

(Contd. on page 5)







Page 5/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 4)

- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

1330-20-7 xylene
IOELV Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin
108-10-1 4-methylpentan-2-one
IOELV Short-term value: 208 mg/m³, 50 ppm
Long-term value: 83 mg/m³, 20 ppm
100-41-4 ethylbenzene
IOELV Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- · Recommended filter device for short term use: Combination filter A-P2
- · Protection of hands:



Protective gloves

Sensibilisation by the components in the glove materials is possible.

(Contd. on page 6)



= FI



Page 6/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 5)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/

the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Use gloves resistant to chemical affects (EN 374) and having CE marking.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Butyl rubber, BR

Fluorocarbon rubber (Viton)

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Neoprene gloves

- · As protection from splashes gloves made of the following materials are suitable: Nitrile rubber, NBR
- · Eye protection:



Tightly sealed goggles

- **Body protection:** Use protective clothing that prevents direct contact to skin.
- · Protective suit antistatic.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 114 °C

(Contd. on page 7)







Page 7/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

	(Contd. of page
· Flash point:	18 °C (Closed cup)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	430 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	1,1 Vol %
Upper:	9,0 Vol %
Vapour pressure at 20 °C:	8 hPa
Density at 20 °C:	0.85 g/cm^3
Relative density	Not determined.
Vapour density	Lighter than air
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Partly soluble.
· Partition coefficient (n-octanol/wa	ter): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	10 s (DIN 53211/4)
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

EII

(Contd. on page 8)





Page 8/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:		
1330-20-7 xylene		
Dermal LD50 2000 mg/kg (rabbit)		
-methylper	ntan-2-one	
LD50	16000 mg/kg (rab)	
LC50/4 h	8,3-16,6 mg/l (rat)	
Hydrocarbons, C9 aromatics		
LD50	>3160 mg/kg (rabbit)	
LC50/4 h	(rat)	
100-41-4 ethylbenzene		
LD50	17800 mg/kg (rabbit)	
	xylene LD50 -methylpen LD50 LC50/4 h ons, C9 an LD50 LC50/4 h thylbenzen	

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- · Serious eye damage/irritation Irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details.

Harmful to aquatic organisms

(Contd. on page 9)



= EU





Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 8)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

					0 0		1	<u> </u>	
I	· European	waste cata	logue						
	15 00 00	WASTE P. PROTECT	ACKAGING, TIVE CLOTH	; ABSORBE HING NOT (NTS, W. OTHER	TPING CL WISE SPE	OTHS, FILTEF CIFIED	R MATERIALS AND	
	15 01 00	packaging	g (including s	separately c	ollected	municipal	packaging was	ste)	
ſ	15 01 10*	packaging	g containing i	residues of	or conta	minated by	y dangerous su	bstances	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: 1	Fransport inj	formation
---------------	---------------	-----------

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
$\cdot ADR$	1263 PAINT, special provision 640D
· IMDG, IATA	PAINT
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	



· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	II
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33

(Contd. on page 10)

EU





Page 10/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

	(Contd. of page
· EMS Number:	F-E, <u>S-E</u>
· 14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.
· Transport/Additional information:	пот аррисаоте.
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· Transport category	2
Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN1263, PAINT, special provision 640D, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:





Xn Harmful F Highly flammable

Hazard-determining components of labelling:

Hydrocarbons, C9 aromatics xylene

· Risk phrases:

11 Highly flammable.

20/21 Harmful by inhalation and in contact with skin.

36/37/38 Irritating to eyes, respiratory system and skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· Safety phrases:

9 Keep container in a well-ventilated place.

15 Keep away from heat.

(Contd. on page 11)





Page 11/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 10)

- 23 Do not breathe gas/fumes/vapour/spray.
- 36/37 Wear suitable protective clothing and gloves.
- 51 Use only in well-ventilated areas.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.
- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R20/21 Harmful by inhalation and in contact with skin.
- R36 Irritating to eyes.
- R36/37 Irritating to eyes and respiratory system.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- *R65* Harmful: may cause lung damage if swallowed.
- *R66* Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department
- · Contact: Ms. Sevde Seza Bozacioğlu
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 12)



= EU



Page 12/12

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.05.2015 Version number 8 Revision: 08.05.2015

Trade name: CARDEA UNIVERSAL THINNER 20 (STD) - 1 L

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* * Data compared to the previous version altered.

EU

